

## Powerful ANPR camera for parking systems



### The CitySync 40 camera is optimised for short to mid-ranged ANPR for the following applications:

- ▶ Airports security and parking
- ▶ Shopping centres
- ▶ Barrier and access control systems

### High Quality Imaging

The CitySync 40 camera provides HD video for high-accuracy ANPR for parking and access control systems.

The 2MP sensor provides detailed images of passing licence plates. The high resolution enables capture of the most challenging plates including those with half-height and stacked characters. It is available with 850nm illumination, which allows clear and crisp licence plate images to be produced 24-hours a day.

The camera is based on a powerful quad core 1.2GHz processing platform and uses Linux operating system for maximum stability and robustness.

### On-board Jet Recognition Engine utilizing deep learning

All the HD video is processed inside the camera housing by the Jet Recognition Engine using our latest advances in deep learning, with no need to send high bandwidth video across the network to high-powered external process PCs. The engine is supported full-time by our in-house development team.

### KEY FEATURES

- ▶ HD ANPR camera for 24/7 plate recognition
- ▶ Captures plates from 3-15 metres
- ▶ IP connectivity
- ▶ Powerful processor running ANPR engine on-board

### JetManagementSuite Software

When combined with the JetManagementSuite software, users are able to experience a complete parking management and access control system. The system allows:

- ▶ Car park counting
- ▶ Automated access / barrier control
- ▶ LED sign integration
- ▶ Alarm management
- ▶ Ticketing integration

PART NO. INFORMATION	DESCRIPTION
CS-40-S-850	3-6 m range with IR
CS-40-M-850	6-10 m range with IR
CS-40-L-850	10-15 m range with IR

## TECHNICAL INFORMATION

<b>Input Power</b>	24-48V DC (Amphenol IP68 M-series connector*) PoE+IEEE 802.3at
<b>Power Consumption</b>	Max 15W
<b>ANPR Range Options</b>	Various from 3m to 15m
<b>ANPR Camera</b>	2MP 1/2.8" CMOS sensor Frame Rate: 25 fps maximum
<b>Illuminators</b>	850nm IR Illumination pre-focused and aligned to suit detection range
<b>Shutter Speed</b>	1/25 <sup>th</sup> –1/8,000 <sup>th</sup> second
<b>Environmental</b>	-30° C to +55°C – operating temperature 0%–95% Relative Humidity
<b>Dimensions and Mass</b>	With sunshield 95 x 198 x 253 mm (H x W x D) 2.62kg Without sunshield 77 x 160 x 185 mm (H x W x D) 1,58 kg
<b>Interfaces</b>	LAN (weatherproof standard RJ45) 10/100Mbps Ethernet interface
<b>CPU</b>	Quad core Cortex A-9 processor @ 1.2GHz
<b>Operating System</b>	Linux
<b>Brackets</b>	Various optional mounts available
<b>Standards</b>	IP66, Ingress protection EN 60950-1, Electrical Safety General IEC 60950-22, Electrical Safety Outdoor EN 55022:2010, Emissions EN 55024:2010, Immunity IEC 60068-2-27 Ea, Shock IEC 60068-2-64 Fh, Vibration UL94 HB, Flammability RoHS directive 2002/95/EC and RoHS2 directive 2011/65/EU

\*Article number 12-03PMMS-SF8001 female to be used on cable.